

GT-ADH210/213

AHD High Definition Analog Cameras

Features

- OV9712/SONY238 sensor
- AHD HD video signal coaxial transmission
- Adopts 75-5 coaxial cable, transmission distance up to 500 meters
- Support 720P@25/30 long distance, real-time transmission in high speed









Specifications

| Model | GT-ADH210 | GT-ADH213 |
|----------------------------|----------------------------------|------------------------|
| Sensor | AHD 2431+OV9712 | AHD 2431+ Sony IMX238 |
| Light-sensing surface area | 1/4-inch | 1/2.8-inch |
| Resolution | 1.0MP | 1.3MP |
| Definition | 1280(H)x720(V) | 1280(H)x960(V) |
| Video Frame | 1280×720@25 fps; 1280×720@30 fps | |
| Frame Rate In Main Stream | 1—4Mbps | 1—5Mbps |
| Min. illumination | IR on: 0 Lux | |
| Lens | 3.6mm (2.8/6.0mm optional) | 3.6mm (6.0mm optional) |
| Signal Noise Ratio | 40dB | 45dB |
| White Balance | Auto | |
| Shutter | Auto | |
| Infrared Resection | IR-CUT | |
| IR Distance | 10m | |
| Power Supply | DC 12V /1.5A | |
| Operating Temperature | -10°C∼+50°C | |
| Net/Gross Weight | 0.38kg/0.48kg | |
| Dimension(color box) | 193mm*105mm*102mm | |