

Biometric Tripod Turnstile



TS2100 Tripod Turnstile TS2111 Tripod Turnstile with Controller and RFID Reader TS2122 Tripod Turnstile with Controller and Fingerprint&RFID Reader

Tripod turnstiles are compact and cost-effective entrance solutions. Designing for smooth and silent operation, reducing power consumption, wear and tear. It is suitable for areas with a high traffic.

The TS2100 series offer a slim, two-legged casework made of stainless steel, ideal for sites where a high traffic and space are issued

By receiving a signal from the access control system, or pushing button, it allows the entry of one person in a time. The status is shown on the led-way mode indicators on the top. Entering into different directions are electronically controlled. Default mode is to lock the mechanism until a valid authorization signal is received. If you want to set one side free, you can have it by adjusting the mechanism. In case of emergency, the horizontal arm will drop to allow free passage. Led way mode indicators are included as standard.

Features



Reliability

- Alloy steel tripod hub prevents mechanical wear
 Casework and tripod arms manufactured in SUS304 stainless steel
- Electromagnets for lock are used only when being activated. They are in standby mode when the device is idle.
- ZK patented compact mechanism ensures
- High quality electrical components







- Drop arm designed for emergency purpose
- No exposed screws, safer for the user.
- Smooth operation designed for mas transit application
 The pictogram on the device indicating access
- The pictogram on the device indicating access permission and direction of movement
- Special designed case shape, user-friendly for passenger to punch card or finger.
- Anti-tailgate



- Flexible reader installation plate. Customers can easily integrate with third party redaer
- Standard electrical interface for third party device.
- Using compact mechanism, the turnstile has more space inside for integration
- ZKTeco provides integration service in factory, with board and peripherals installed, ensuring compliance of the system. When the turnstile is delivered, just plug it in and do the setting. Save the cost of installation.
- The design of being vacuum at the bottom part of the device, enables easy installation for other hardwares.





Specifications

Power Supply	AC 220V/110V, 50/60Hz
Operating Temperature	-28 °C- 60 °C
Operating Humidity	5%-85%
Working Environment	Indoor/Outdoor(shelter)
Rated Power	60W
Flow Rate	25-48 passage/minute
Ingress Protection	IP54
Casework Material	SUS304
Pictogram Indication	Yes
Control System	Input controlled by dry contact
Emergency Button Input	Yes
Dimension	111×98×18(CM) + arm length 50CM
Package Dimension	120×108×28(CM)
Net Weight	45KG
Gross Weight with Package	53KG
Optional Function	Alternative material or shape, third-party access control integration,
	ticket system integration, passage counter

Dimensions (mm)







ZKTeco Inc. ZK Mansion, Wuhe Rd, Gangtou, Bantian, Buji Town, Longgang District, Shenzhen China 518129

Tel: 86-755-8960 2345/46/47/48 E-mail: sales@zkteco.com www.zkteco.com

Global Offices: USA: + 1 732-412-6007 EU: +34 916532891 Brazil: +55 31 2515-832

EU: +34 916532891 Brazil: +55 31 2515-8326 Thailand: +66-027199154 Mexico: +52-55-52928418 South Africa: +27 12 259 1047 Egypt: +201110444134 Dubai: +971 4 6091 310 India: +91 8123536788 Indonesia: +62 21 2921 8949 Vietnam : +84-0169-5813007 Philippines: +63 9084118832 Russia: +8 915 178-46-81

© Copyright 2014. ZKTeco Inc. ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.

